

CREATON PV-AUTARQ. Solar roof tiles powered by Autarq.

Designed, manufactured and refined in Europe.

All benefits at a glance.



Flexible

Solar roof tiles are suitable even for complex roof surfaces



Durable

Just as reliable as the manufacturer's original roof tiles



Weatherproof

Tile impermeability and water drainage remain intact



High quality

Same materials as used in conventional solar modules



Plug-and-play installation

Even without prior electrical knowledge



Traditional workflow

Solar tiles and regular tiles are installed at the same time



Fully intact roof

Perfectly ventilated, without drilling or screws



High safety and fire protection

Through safe low voltage range



Service-friendly

No electronics on the roof, tiles can be replaced at any time

Colours



FINESSE black glaze



NUANCE black engobe



NUANCE copper red engobe

Set yourself free. Request a non-binding offer.



autarq.com

Technical Data

Electrical Data (STC)	CREATON PV-AUTARQ FINESSE black glaze & NUANCE black engobe	CREATON PV-AUTARQ NUANCE copper red engobe
Nominal output power P_{MPP}	10 W	8 W
Nominal voltage U_{MPP}	41 V	41 V
Nominal current I_{MPP}	0.245 A	0.195 A
Open circuit voltage U_{OC}	49 V	49 V
Short-circuit current I_{SC}	0.255 A	0.205 A
Temperature coefficient	-0.40 %/K	-0.40 %/K

Electrical data are average values (+/- 5 %), measured under standard test conditions (STC): 1000 W/m², 25 °C, AM 1.5 (Reference measurement by Fraunhofer ISE Freiburg, Germany)

Material Data	Solar Roof Tiles and Roof
Dimensions	257 x 437 mm
Solar module size	210 x 330 mm
Mechanical strength	5400 Pa, hail- and snowproof, walkable
Tile material	Clay
Front glass	3.2 mm toughened structured solar glass (ESG)
Solar cells	Monocrystalline silicon solar cells
Composite materials	EVA, polyolefins, silicone
Connector	Proprietary plug system, UV-resistant
Connection cable	2 x 0.75 mm ² solar cable in compliance with EN50618 H1Z2Z2-K
Operating temperature	-40 bis +85 °C
Covering capacity	12 tiles/m ²
Recommended batten size	40 x 60 mm
Cover length Exact batten spacing is mandatory	352 +/- 2 mm
Cover width	224–226 mm
Weight	4.9 kg
Roof pitch	15–80°
Recommended roofing	Off-centre
Colours	FINESSE black glaze, NUANCE black engobe, NUANCE copper red engobe
Tiles per package	Packs of four

For further data on the CREATON PV-AUTARQ tile and installation details, please refer to the original data sheets and installation manual by CREATON.

Guarantee and Certification	
Product warranty	5 years
Performance guarantee	25 years, 80 % electrical power output
Applicable standards	IEC 61215, IEC 61730
Hail resistance class	3
Fire safety	Extra low voltage in compliance with VDE 0100-712
Fire resistance classification in compliance with EN 13501-5	B _{ROOF} (t1) – hard roof, not flammable

In partnership with:

Autarq GmbH, Brüssower Allee 87, 17291 Prenzlau, Germany
CREATON GmbH, Dillinger Straße 60, 86637 Wertingen, Germany

www.creaton.de / www.creaton.at / www.creaton.ch / www.autarq.com



Version 9/2023. Technical changes and errors may occur.